

HDMI EXTENDER WITH KVM SUPPORT

Model Code: LKV373KVM

This is a HDMI KVM EXTENDER, is made up of a transmitter unit (local site) and a receiver unit (remote site). The HDMI signal can be extended up to 120 meters via network cable, and the resolution supported is up to 1080p@60Hz. It allows access to a computer system from a remote console by USB connectors(USB keyboard and mouse). It is perfect for factory and construction sites, or any type of installation where the console needs to be in a conveniently accessible location. It is also useful for control and security purposes. Therefore it is widely used in command center, data control center, operation rooms in military, bank, government, enterprise etc



LKV373KVM (RX)



LKV373KVM (TX)

Features:

- Extend HDMI signal up to 120 meters via a single network cable
- High resolution supported is up to 1080p@60Hz
- LED indicators, know the status of power and USB connection easily
- Support KVM function, remote control conveniently
- Support LAN standard 802.3 Ethernet 10/100/1000Mbps
- Compliant STP and UTP CAT5/5E/6 network cables
- Aluminium alloy housing design, stable and durable
- KiT includes 1 x RX and 1 x TX

Specifications

HDMI version	HDMI 1.3
HDCP version	HDCP 1.2
Video bandwidth	≤70Mbps
HDMI resolution supported	640x480@60Hz 800x600@60Hz 1024x768@60Hz 1280x720@60Hz 1360x768@60Hz 1440x900@60Hz 1400x1050@60Hz 1680x1050@60Hz 1920x1080@60Hz
Audio supported	PCM (44.1KHz, 48KHz)
HDMI connector	Type A ,19 pin, Female
LAN connector	RJ-45
Operation temperature	0°C ~ 50°C
Relative humidity	10-95% (Non-condensing)
Power supply	5V/1Ax2pcs
Power Consumption	TX<3.5w RX<3.5w
Dimensions	109.6(L) x 89.5(W) x 26.3(H)mm x2pcs
Weight	TX:160g RX:170g
Colour	Black