

PRODUCT SPECIFICATION

FEATURES:

- Current Meter: Digital True RMS Current Meter
- Power Monitor: Remote Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
- Protocols: Http, Https, SNMP, DHCP, UDP
- Outlet Control: Individual Outlet Control
- Power Delay: Power On/Off Sequence can be Defined
- Alarm Thresholds: User-Defined Alarm Thresholds for Warning and Overload
- Event Alert: Email, Trap, Audible Alarm

GENERAL:

- Output: (14) IEC 320 C13, (2) IEC320 C19
- Input: (1) IEC320 309 attached power cord, 3M
- Protection: (2) 16 AMP Circuit Breaker



COMMUNICATION:

- SSL Indication: (1) Yellow LED
- DHCP Indication: (1) Green LED
- Circuit Status: (2) Red LED
- Output Status: (16) Green LED
- Network: (1) RJ45 for Ethernet
- Temp./Humidity: (1) RJ11 for ENV probe connection
- PDU ID: 1 Digits Seven Segment for PDU Identification
- Current Meter: 3 Digits Seven Segments for True RMS Meter
 - Range: 0A ~ 20 A
 - Resolution: 0.1A
 - Precision: +/-2%/+/-0.1AMP



OPERATION:

- Nominal Voltage: 230V
- Voltage: 200V~ 240V full range
- Frequency: 50/60HZ full range
- Max. Output Current: 32 Amp
- Temperature: 0 ~ 40 Celsius degree
- Humidity: 0% ~ 90%
- Size: 56 x 1245 x 44 mm
- Weight: 4kg

REGULATORY APPROVALS:

- CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 C-Tick AS/NZS CISPR 22: 2006
- FCC Part 15 Class A, ICES-003

