

Line Interactive UPS System

MODEL CODE	TYPE	# SOCKETS
------------	------	-----------

UPS600CL	Dynamix 600VA UPS	2
UPS1000CL	Dynamix 1000VA UPS	4
UPS12V7	12V 7.0AH replacement UPS battery for UPS600CL, UPS1000CL	

FEATURES

- Complete power conditioner and UPS
- New Zealand power sockets on UPS for easy installation
- Clear LED display
- Line interactive, lengthens battery life
- AVR function, ensures stable voltage
- Fax/Phone protection ports
- RS232 communication port and monitoring/shut down software included
- Overload and self diagnostic protection
- 1 Year Warranty



Line Interactive SOHO UPS

MODEL CODE	TYPE
------------	------

UPS650HP	Dynamix 600VA UPS
UPS12V7	12V 7.0AH replacement UPS battery for UPS650HP

FEATURES

- 4 ports backup & 2 ports surge protection
- Complete power conditioner and UPS
- New Zealand power sockets on UPS for easy installation
- Line interactive, lengthens battery life
- AVR function, ensures stable voltage
- Fax/Phone protection ports
- USB communication port and monitoring/shut down software included
- Overload and self diagnostic protection
- 1 Year Warranty



CHARACTERISTIC		SPECIFICATION		
Model		UPS600CL	UPS1000CL	UPS650HP
Rated Power		600VA / 300W	1000VA / 600W	600VA / 360W
No. of Sockets		2	4	4 + 2
Frequency		50/60 Hz		
Battery	Type	Sealed, maintenance-free lead acid		
	Capacity	12V 7 Ah x 1pc	12V 7 Ah x 2pcs	12V 7 Ah x 1pc
	Back-up Time (half load)	>8mins	>12mins	>6mins
	Typical Recharge Time	8-10 hours		10-12 hours
LCD Indicators	Status	NORMAL, FAULT, BATTERY, CHARGE, OVERLOAD		NA
Audible Alarm	Battery Mode	Beeping sound every four seconds, every second if approaching final discharge		
	Overload	Continuous beeping sound		
Audible Noise (1 metre)		< 40dB (A)	< 45dB (A)	< 40dB (A)
Protection	Surge Protection and Filtering	High Voltage, Low Voltage, Surge, Spike		
Environment	Operating Temperature	0 - 40°C		
	Storage Temperature	-15°C ~ 45°C		
	Operating Relative Humidity	10%RH ~ 95%RH: Non-condensing		
Transfer Time		< 10 ms		
Net Weight		6.8kg	13.0kg	6.0 Kgs
Dimension (W x D x H)		86 x 330 x 150mm	120 x 300 x 190mm	515mm X 110mm X 91mm